

Intrinsically safe repeater power supply

For applications in hazardous areas

Model IS Barrier

WIKA data sheet AC 80.14



Applications

- Chemical, petrochemical industry
- Oil, natural gas
- Machine building

Special features

- Input 0/4 ... 20 mA, supplying and non-supplying
- Suitable for SIL 2 per IEC 61508/IEC 61511
- Bidirectional HART® signal transmission



Intrinsically safe repeater power supply model IS barrier

Description

The model IS barrier intrinsically safe repeater power supply has been designed for applications in combination with intrinsically safe 4 ... 20 mA sensors.

By using different connection terminals, 2-wire as well as 4-wire transmitters can be connected.

The analogue measured value is transmitted to the non-hazardous area, galvanically isolated from the hazardous area. On the output side, the repeater power supply can be operated as supplying or non-supplying.

The test sockets contained in the COMBICON connectors enable the direct connection of HART® communicators.

The repeater power supply has been tested for operation with the following WIKA products:

- | | | |
|---------|----------|----------|
| ■ LH-20 | ■ IS-21 | ■ UPT-2x |
| ■ IL-10 | ■ IPT-1x | ■ T24 |
| ■ IS-3 | ■ DPT-1x | ■ T32 |
| ■ IS-20 | | |

In intrinsically safe circuits, the repeater power supply enables the safe operation of these products. A template to create the proof of intrinsic safety can be found at www.wika.com.

Input

Input

Active current input, intrinsically safe

Input signal, current

4 ... 20 mA

Current limitation

25 mA

Transmitter power supply

> DC 16 V (for 20 mA)

> DC 15.3 V (for 22.5 mA)

Under and overload signal range

0 ... 24 mA (extended transmission range for diagnostics)

Output

Output

Current output (active and passive)

Transfer 1 : 1 to input signal

Under and overload signal range

0 ... 24 mA (extended transmission range for diagnostics)

Load

< 1,000 Ω at 20 mA

< 825 Ω at 24 mA

Output ripple

< 20 mV_{eff}

Behaviour in the event of an error in accordance with NE43

0 mA (cable break in input)

≥ 22.5 mA (cable short circuit in input)

Galvanic isolation

Input / Output / Voltage supply

Insulation voltage: 300 V_{eff}

Overvoltage category II

Pollution degree 2

Safe isolation in accordance with EN 61010-1: 50 Hz, 1 min.

Test voltage: 2.5 kV

Input / Output

Voltage peak value in accordance with EN 60079-11: 375 V

Input / Voltage supply

Voltage peak value in accordance with EN 60079-11: 375 V

Voltage supply

Power supply

Nominal voltage: DC 24 V

Voltage range: DC 19.2 ... 30 V

Max. current supply

< 76 mA (DC 24 V / 20 mA / 1,000 Ω)

< 55 mA (DC 24 V / 20 mA / 250 Ω)

Dissipation loss

Output, active: < 1.1 W (DC 24 V / 20 mA / 1,000 Ω)

< 0.95 W (DC 24 V / 20 mA / 250 Ω)

Output, passive: < 1.2 W (DC 24 V / 20 mA / 0 Ω)

Power consumption (output active)

< 1.8 W (20 mA / 1,000 Ω)

< 1.3 W (20 mA / 250 Ω)

Accuracy specifications

Transmission error

< 0.05 % of end value (typ.)

< 0.10 % of end value (max.)

Temperature coefficient

< 0.004 %/K (typ.)

< 0.01 %/K (max.)

Step response (10 ... 90 %)

< 200 μ s (with step 4 mA ... 20 mA, load 600 Ω)

< 600 μ s (with step 0 mA ... 20 mA, load 600 Ω)

Operating conditions

Ingress protection

IP 20

Overvoltage category

II

Flammability class in accordance with UL 94

V0

Pollution degree

2

Permissible ambient temperatures

Operation: -20 ... +60 °C

Storage: -40 ... +80 °C

Permissible humidity

10 ... 95 % (no condensation)

Mounting position

as required

Materials

Case

PA 66-FR, anthracite grey (RAL 7016)

Electrical connections

Diameter of the test socket

2 mm

Wire cross-section

Rigid wire 0.2 ... 2.5 mm²

Flexible wire 0.2 ... 2.5 mm²

AWG 24 ... 14

Stripped length

7 mm

Tightening torque

0.5 ... 0.6 Nm

Reverse polarity protection

yes

HART[®] communication

Supported protocols

HART[®]

Signal bandwidth

corresponding to HART[®] specification

Safety-related data in accordance with ATEX

Operating mode

Supply isolated amplifier

Max. output voltage U_0

DC 25.2 V

Max. output current I_0

93 mA

Max. output power P_0

587 mW

Group

(Max. external inductance L_0 / Max. external capacitance C_0)

IIB: 4 mH / 820 nF

IIC: 2 mH / 107 nF

Maximum voltage U_m

AC 253 V / DC 125 V

Ignition protection types

ATEX

■ II (1) G [Ex ia Ga] IIC/IIB

■ II (1) D [Ex ia Da] IIC

■ II 3 (1) G Ex nA [ia Ga] IIC/IIB T4 Gc

■ I (M1) [Ex ia Ma] I

IECEX

■ [Ex ia Ga] IIC/IIB

■ [Ex ia Da] IIC

■ Ex nA [ia Ga] IIC/IIB T4 Gc

■ [Ex ia Ma] I

cULus

■ UL 61010 Listed

■ Class I, Div. 2, Groups A, B, C, D T4

■ Class I, Div. 2, Groups IIC, IIB, IIA T4

■ Associated apparatus for use in Class I, Division 1, Groups A,B,C,D

■ Associated apparatus for use in Class II, Div.1 Groups E,F,D




■ Associated apparatus for use in Class III, Division 1

■ Associated apparatus for use in Class I, Zone 0,1,2, Groups IIC,IIB,IIA

Dimensions in mm

W x H x D: 12.5 x 99 x 114.5 mm (without connection terminals)

Approvals

Logo	Description	Country
	EC declaration of conformity <ul style="list-style-type: none"> ■ EMC directive 2004/108/EC, interference immunity in accordance with EN 61000-6-2 During the interference, small deviations can occur Radiated emission in accordance with EN 61000-6-4 ■ ATEX directive 94/9/EC II (1) G [Ex ia Ga] IIC/IIB II (1) D [Ex ia Da] IIC II 3 (1) G Ex nA [ia Ga] IIC/IIB T4 Gc I (M1) [Ex ia Ma] I 	European Community
	IECEX Hazardous areas <ul style="list-style-type: none"> ■ [Ex ia Ga] IIC/IIB ■ [Ex ia Da] IIC ■ Ex nA [ia Ga] IIC/IIB T4 Gc ■ [Ex ia Ma] I 	IECEX member states
	UL Safety (e.g. electr. safety, overpressure, ...) <p>Hazardous areas</p> <ul style="list-style-type: none"> ■ Class I, Div. 2, Groups A, B, C, D T4 ■ Class I, Div. 2, Groups IIC, IIB, IIA T4 ■ Associated apparatus for use in Class I, Division 1, Groups A,B,C,D ■ Associated apparatus for use in Class II, Div.1 Groups E,F,D ■ Associated apparatus for use in Class III, Division 1 ■ Associated apparatus for use in Class I, Zone 0,1,2, Groups IIC,IIB,IIA 	USA and Canada

Manufacturer's information and certifications

Logo	Description
	SIL 2 Functional safety

Approvals and certificates, see website

Ordering information

Order number 14117118

© 2015 WIKA Alexander Wiegand SE & Co. KG, all rights reserved.
The specifications given in this document represent the state of engineering at the time of publishing.
We reserve the right to make modifications to the specifications and materials.

