


2, 3, and 4-Wire Washdown Cordsets

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection
- Polypropylene Contact Holder, Mold Material and Cable Jacket
- High Chemical Solvent Resistance & Tensile Strength



Connector Style	Female Part Number	Male Part Number	Features	Pinout
<p>WD-RKV ..**</p>	WD-RKV 20-*M WD-WKV 20-*M	WD-RSV 20-*M WD-WSV 20-*M	PP White, 2x18 AWG, 105°C, 300 V, 9 A, 5.1 mm OD, Cable #RF51441-*M	1. BN 2. BU Female
	WD-RKV 26-*M WD-WKV 26-*M	WD-RSV 26-*M WD-WSV 26-*M	PP White, 2x16 AWG, 105°C, 600 V, 10 A, 6.2 mm OD, Cable #RF51442-*M	1. WH 2. BK
<p>WD-WKV ..**</p>	WD-RKV 30-*M WD-WKV 30-*M	WD-RSV 30-*M WD-WSV 30-*M	PP White, 3x18 AWG, 105°C, 300 V, 9 A, 5.7 mm OD, Cable #RF51443-*M	1. GN/YE 2. BN 3. BU Female
	WD-RKV 36-*M WD-WKV 36-*M	WD-RSV 36-*M WD-WSV 36-*M	PP White, 3x16 AWG, 105°C, 600 V, 10 A, 7.2 mm OD, Cable #RF51444-*M	1. GN 2. BK 3. WH Male
<p>WD-RSV ..**</p>	WD-RKV 40-*M WD-WKV 40-*M	WD-RSV 40-*M WD-WSV 40-*M	PP White, 4x18 AWG, 105°C, 300 V, 9 A, 6.2 mm OD, Cable #RF51445-*M	1. BN 2. WH 3. BU 4. BK Female
	WD-RKV 46-*M WD-WKV 46-*M	WD-RSV 46-*M WD-WSV 46-*M	PP White, 4x16 AWG, 105°C, 600 V, 10 A, 7.2 mm OD, Cable #RF51446-*M	1. BK 2. WH 3. RD 4. GN Male
<p>WD-WSV ..**</p>	WD-RKV 46-*M WD-WKV 46-*M	WD-RSV 46-*M WD-WSV 46-*M	PP White, 4x16 AWG, 105°C, 600 V, 10 A, 7.2 mm OD, Cable #RF51446-*M	1. BK 2. WH 3. RD 4. GN Female
				Male

* Length in meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is stainless steel.