



5-Wire Cordsets, "C" Style Medium Plug Body

- NEMA 1, 3, 4, 6P
- IEC IP68 Protection
- 250 V, 4 A



Connector Style	Female Part Number	Male Part Number	Features	Pinout
<p>RKC ..**</p>	<p>RKC 4.5T-*/S653 WKC 4.5T-*/S653</p>	<p>RSC 4.5T-*/S653 WSC 4.5T-*/S653</p>	<p>ITC/PLTC AWM PVC Grey, 4x22 AWG, 105°C, Foil/Drain, 5.1 mm OD, Cable #RF50773-*M†, RFI/EMI Shielding, Tray Rated</p>	<p>1. BN 2. WH 3. BU 4. BK 5. Drain</p>
<p>WKC ..**</p>	<p>RKC 4.5T-*/S1538 WKC 4.5T-*/S1538</p>	<p>RSC 4.5T-*/S1538 WSC 4.5T-*/S1538</p>	<p>AWM PVC Grey, 5x18 AWG, 105°C, 7.2 mm OD, Cable #RF50630-*M†, flexlife*</p>	<p>1. BN 2. WH 3. BU 4. BK 5. GN/YE</p>
<p>RKC ..**</p>	<p>RKC 4.5T-*/S1062 WKC 4.5T-*/S1062</p>	<p>RSC 4.5T-*/S1062 WSC 4.5T-*/S1062</p>	<p>AWM PVC Yellow, 5x22 AWG, 105°C, 5.7 mm OD, Cable #RF50684-*M†, flexlife</p>	<p>1. BN 2. WH 3. BU 4. BK 5. GY</p>
<p>RSC ..**</p>	<p>RKC 4.5T-*/CS10288 WKC 4.5T-*/CS10288</p>	<p>RSC 4.5T-*/CS10288 WSC 4.5T-*/CS10288</p>	<p>AWM PVC Yellow, 5x18 AWG, 105°C, 7.2 mm OD, Cable #RF50549-*M†, flexlife*</p>	<p>1. BN 2. WH 3. BU 4. BK 5. GN/YE</p>
<p>WSC ..**</p>	<p>RKC 4.5T-*/S1062 WKC 4.5T-*/S1062</p>	<p>RSC 4.5T-*/S1062 WSC 4.5T-*/S1062</p>	<p>AWM PVC Grey, 5x22 AWG, 105°C, 5.7 mm OD, Cable #RF50543-*M†, flexlife* Cable, PVC plug body with PVC contact carriers</p>	<p>1. BN 2. WH 3. BU 4. BK 5. GY</p>
<p>RSC ..**</p>	<p>RKC 4.5T-*/S1587 WKC 4.5T-*/S1587</p>	<p>RSC 4.5T-*/S1587 WSC 4.5T-*/S1587</p>	<p>AWM TPE Yellow, 5x18 AWG, 105°C, 6.4 mm OD, Cable #RF51232-*M†, weldlife, Weld Flash Immune</p>	<p>1. BN 2. WH 3. BU 4. BK 5. GY</p>
<p>WSC ..**</p>	<p>RKC 4.5T-*/S1587 WKC 4.5T-*/S1587</p>	<p>RSC 4.5T-*/S1587 WSC 4.5T-*/S1587</p>	<p>ITC/PLTC PVC NAMUR Blue, 5x22 AWG, 105°C, 6.9 mm OD, Cable #RF50767-*M†, flexlife*, for VBN 40-H1141 MultiBox</p>	<p>1. GN 2. WH 3. OG 4. BK 5. RD</p>



* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "RKC .."; "RKC .." indicates stainless steel.

† See Section N for **reelfast**® cable information.