

12-Wire Cordsets, "C" Style Medium Plug Body

- NEMA 1, 3, 4, 6P
- IEC IP68 Protection
- 60 VAC/75 VDC, 2 A



Connector Style	Female Part Number	Male Part Number	Features	Pinout
<p>RKC ..**</p>	RKC 12T-* WKC 12T-*	RSC 12T-* WSC 12T-*	AWM PVC Grey, 12x24 AWG, 105°C, 6.3 mm OD, Cable #RF50991-*M†, flexlife®	<p>Female</p> <p>Male</p>
<p>WKC ..**</p>	RKC 12T-*/S90 WKC 12T-*/S90	RSC 12T-*/S90 WSC 12T-*/S90	AWM TPU Grey, 12x24 AWG, 90°C, 6.0 mm OD, Cable #RF50990-*M†, Cut/Abrasion Immune	
<p>RSC ..**</p>	RKC 12T-*/S101 WKC 12T-*/S101	RSC 12T-*/S101 WSC 12T-*/S101	AWM TPE Black, 12x24 AWG, 105°C, 7.0 mm OD, Cable #RF50943-*M†, flexLife-20, High Flex Over 20 Million Cycles	
<p>WSC ..</p>	RKC 12T-*/S618 WKC 12T-*/S618	RSC 12T-*/S618 WSC 12T-*/S618	AWM PVC Black, 12x24 AWG Foil/Drain, 105°C, 7.0 mm OD, Cable #RF50755-*M†, RFI/EMI Shielding	

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "RKC .."; "RKC .." indicates stainless steel.

† See Section N for **reelfast**® cable information.