Ralston Instruments

www.ralstoninst.com

Part No.

LC10-GR2M

LC10 pressure gauge, 3000 psi / 200 bar / 20 MPa, 1/4" Male NPT bottom connection

The LC10 is a robust device that measures and displays pressure readings on a large, backlighted screen. The LC10 has the ability to show High and Low pressure values on-screen, change between 15 different engineering units or add custom engineering units. The included PC FieldLab Desktop software can be used for calibration, testing and live viewing of pressure.



LC10-GR2M

2 **Battery Count Battery Life** 1500 Hours Battery Type AA Alkaline (LR6) **Burst Pressure** 12000 PSI / 825 bar / 83 MPa Certifications Certified to CSA Standard C22.2 No. 61010-1, Conforms to UL / IEC / EN / AS Standard No. 61010-1, Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU Country of origin USA Electrical Rating 50 mA @ 5 VDC atm, bar, cmH2O @4°C, inH2O @39°C, kPa, MPa, psi, inHg @39°F, kgf / cm^2, ftH2O @39°F, cmHg @ **Engineering Units** 0°C, oz / sqin IP67 (1 meter water submersion for 30 minutes) **Ingress Protection** LCD Display 2.4 in / 61 mm segmented LCD Display Materials ABS / Polycarbonate Blend, Powder Coated Aluminum 120 °F / 50 °C Max Operating Temperature Max Pressure 3000 PSI / 200 bar / 20 MPa 165 °F / 75 °C Max Storage Temperature Measurement Type **Gauge Pressure** Measurement +/- 0.25% of Full Scale (ASME Grade 3A/ISO Class 0.25) Uncertainty Media Compatibility Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Mineral Oil, Natural Gas, Petroleum Based Oil, Skydrol, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil, Water

Specs/Attributes

Ralston Instruments Inc. | ralstoninst.com | Toll Free 800-347-6575 | Phone 440-564-1430 | Fax 440-564-1480

R Ralston Instruments

Specs/Attributes

Min Operating Temperature	-4 °F / -20 °C
Min Storage Temperature	-40 °F / -40 °C
Operating Altitude (max)	10,000 ft (3050 m)
Process Connection	1/4" Male NPT
Protection Class	Pollution Degree 2 (UL / IEC 61010-1)
Relative Humidity	0% to 90% (-10 to 35°C) , 0% to 70% (35 to 50°C)
USB Connection	USB (Micro B)
Wetted Materials	316 Stainless Steel
Wrench Size	7/8 ln 23 mm
Weight	12.6 oz / 355 grams
Dimensions	H: 1.75 in (4.45 cm) x W: 3.4 in (8.64 cm) x D: 4.1 in (10.41 cm)