

# TURCK 7/8" minifast® Connectivity Products



## 2 and 3-Wire Receptacles, Front Mount, 1/2-14 NPT Threads

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection



Housing Style	Female Part Number	Male Part Number	Features	Pinout
<p><b>RKF ..NPT</b></p> <p>Typical panel cutout 22.5 mm</p> <p><b>RSF ..NPT</b></p> <p>Typical panel cutout is 22.5 mm</p>	RKF 20-*M/NPT	RSF 20-*M/NPT	2x18 AWG, 105°C, 9 A, standard duty	1. BN 2. BU
	RKF 26-*M/NPT	RSF 26-*M/NPT	2x16 AWG Leads, 105°C, 10 A, heavy duty	1. WH 2. BK
	RKF 28-*M/NPT	RSF 28-*M/NPT	2x18 AWG, 105°C, 600 V, 9 A, heavy duty	1. WH 2. BK
	RKF 30-*M/NPT	RSF 30-*M/NPT	3x18 AWG, 105°C, 9 A, standard duty	1. GY/YE 2. BN 3. BU
	RKF 31-*M/NPT	RSF 31-*M/NPT	3x18 AWG, 105°C, 9 A, standard duty	1. BK 2. BN 3. BU
	RKF 311-*M/NPT	RSF 311-*M/NPT	3x18 AWG, 105°C, 9 A, automotive color code	1. GN 2. RD/BK 3. RD/WH
	RKF 35-*M/NPT	RSF 35-*M/NPT	3x16 AWG, 105°C, 10 A, automotive color code	1. GN 2. BK 3. WH
	RKF 36-*M/NPT	RSF 36-*M/NPT	3x16 AWG, 105°C, 10 A, heavy duty	1. GN 2. BK 3. WH
	RKF 38-*M/NPT	RSF 38-*M/NPT	3x18 AWG, 105°C, 600 V, 9 A, heavy duty	1. GN 2. BK 3. WH

Receptacles

Standard lead length is 0.3 Meters. Consult factory for other lengths.  
 \*\* Standard housing material is nickel plated brass.. "RSF .."; "RSFV .." indicates stainless steel housing.  
 For locknuts to be included, add "W/LN" to the end of the part number.  
 To specify PVC jacketed cable, add "/S717" to the end of the part number.